



NO.10, LN.630, JIANGCHENG RD., EAST  
DIST., TAICHUNG CITY  
40150, TAIWAN  
TEL : 04-22802156  
FAX : 04-22802132  
E-MAIL : core.focus156@gmail.com  
<https://www.cf-lights.com>

# SPECIFICATION

PART NO.: CF-FCS 系列

天井燈

200W


一、圖面外觀




二、規格

品牌		
產品名稱	LED 天井燈	
產品型號	CF-FCS-200W	
消耗功率	200W	
燈珠品牌		
光效	≥ 125 lm/W	≥ 140 lm/W
LED 光通量	≥ 25000 LM±5%	≥ 28000 LM±5%
色溫	白光、黃光	
燈具材質	鋁壓鑄、PC	
電源	防水集成寬壓恆流電源	
輸入電壓	AC85~265V	
電源頻率	50Hz~60Hz	
防護等級	IP 65	
保固期限	保固二年	
尺寸	Φ360mm*155mm	
重量	3.75kg	
尺寸圖		

## 三、數據

PART NO.:CF-FCS-200W						
Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Luminous Flux 	$\Phi_v$	85-265 VAC	21210	25000		Lm
Color Index	%	85-265 VAC				Ra
Illuminance@1M distance		85-265 VAC	9471	11160		Lux
Illuminance@8M distance		85-265 VAC	200	235		Lux
Illuminance@10M distance		85-265 VAC	150	177		Lux
Illuminance@12M distance		85-265 VAC	104	123		Lux
Illuminance@15M distance		85-265 VAC	67	77		Lux
Power Consumption	P <sub>D</sub>	85-265 VAC		200	215	W
Power Factor		85-265 VAC	0.92	0.95		
Finished weight				3.75	3.95	kg

PART NO.:CF-FCS-200W						
Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Luminous Flux 	$\Phi_v$	85-265 VAC	23756	28000		Lm
Color Index	%	85-265 VAC				Ra
Illuminance@1M distance		85-265 VAC	10607	12500		Lux
Illuminance@8M distance		85-265 VAC	224	264		Lux
Illuminance@10M distance		85-265 VAC	168	198		Lux
Illuminance@12M distance		85-265 VAC	117	138		Lux
Illuminance@15M distance		85-265 VAC	75	86		Lux
Power Consumption	P <sub>D</sub>	85-265 VAC		200	215	W
Power Factor		85-265 VAC	0.92	0.95		
Finished weight				3.75	3.95	kg